



INNOVATIONS FOR LIVING™

PINKWRAP® HOUSEWRAP (STANDARD FEATURE)

INSULATION



Serious protection for weather-wise homes.

Typically installed over wood or insulating sheathing, and under siding or other exterior covering, PINKWRAP® surrounds your home

with a protective barrier to help seal out energy-robbing leaks and drafts (air infiltration). Working hand-in-hand with insulation, which traps air in tiny pockets to slow the transfer of heat (thermal control), PINKWRAP functions like a windbreaker layered over a thick sweater to keep your home comfortable and energy efficient throughout the year.

Controlling moisture in a humid environment.

The average daily activities inside a home—showering, cooking, washing clothes and dishes, even breathing—produce moisture vapor which needs to escape. PINKWRAP housewrap is specially engineered to stop air infiltration while, at the same time, allowing excess moisture to be “exhaled” so it won’t build up in walls.

Built to Handle Tough Construction Conditions.

PINKWRAP is specially designed to resist tearing around nail and staple holes, even in windy conditions.



INSTALLATION & FEATURES

1. Attach underneath or over sheathing board or insulation. PINKWRAP is translucent to help you see your alignments.
2. To begin wrapping, start at the base of the wall, 2 to 3 feet from a corner. Fold 3 to 5 inches of PINKWRAP under itself and fasten to a stud or framing member, printed side out. Installation Wrap the entire building, including door and window openings.
3. Staples (galvanized 16 gauge) or nails (3/8 inch diameter) may be used for attachment to structural materials such as framing members or plywood. When covering non-structural sheathing (such as foam plastic insulation boards) nail through sheathing and into studs using large head fasteners or nails with plastic heads. Fasteners should penetrate a minimum of 1/2 inch into studs.
4. To hold PINKWRAP housewrap in place: * 9-foot roll: Place a minimum of three fasteners (one at top, middle and bottom). * 3-foot roll: Place a minimum of two fasteners (one at top and bottom).
5. Fastening Once PINKWRAP housewrap is in place, fasteners should be placed every six inches at the perimeter of the wall and around door and window openings, and should be spaced every 12 - 16 inches along vertical framing members.
6. At the end of a roll, fold the edge under and fasten to the nearest stud or framing member. To minimize air infiltration, overlap PINKWRAP at least 8 inches on all horizontal and vertical seams, with the upper layer overlapping the lower layer. For upper stories, a 12-inch overlap over the story below is necessary.

**PINKWRAP®
Housewrap**

Application(s)
Exterior Walls

Width x Length

- 3' x 100'
- 9' x 100'
- 9' x 195'

